



## WALL-MOUNTED PORCELAIN SHAMPOO BOWL

SKU:CB80

Wall-Mounted Porcelain Shampoo Bowl

### TECHNICAL INFORMATION

---

- Measures: Large 19"W x 20"D x 10"H
- 570 Faucet
- Spray hose
- Vacuum breaker
- Drain assembly
- UPC approved
- Shown w/ optional neck rest in second picture

### SHIPPING INFORMATION

---

Item generally ships via Freight(Truck) service

- Weight: 62 lbs
- Dimensions: 26"L x 26"W x 25"H

### WARRANTY

---

#### 5 YEARS:

- Collins ABS Shampoo Bowls

#### 2 YEARS:

- Collins-Jeffco faucets and Porcelain Shampoo Bowls


#### 1 YEAR:

- All remaining components, unless noted otherwise, are guaranteed for a period of one year from the date of purchase.




## CB80-B / CB80-W Shampoo Bowl Installation

Install the wall bracket so that the top edge (cross bar) is 30 ¼" from the finished floor. This bracket height is suggested to obtain the most common neckrest height. However, the bracket height may be varied to accommodate personal preference and/or height needed for shampoo/AP chair to be used with bowl.




Place bowl into bracket to ensure location is adequate. Be sure bowl is level side to side. If so, peel the top coat of the double-sided tape on the bracket, and place bowl into place. Apply small bead of silicone to the back edge of the bowl (as well as to the sides of bowl for in-cabinet mounting).




## HOSE CONNECTIONS

If your Bowl is equipped with a Vacuum Breaker, connect one end of the Fixture Hose to the inlet side of the Vacuum Breaker. Connect the other end to the Fixture Tailpiece. Attach the Spray Hose connector to the Vacuum Breaker outlet.




## INSTALL THE DRAIN ASSEMBLY

Apply a liberal amount of plumber's putty around the top of the drain opening.




3 1/2" APPROVED DRAIN ASSEMBLY REQUIRED.


Place the Strainer Body in the opening, and press it into the plumber's putty.





If your Bowl is *not* equipped with a Vacuum Breaker attach the Spray Hose connector to the fixture tailpiece.



From the underside of the Bowl, place the Fiber and Rubber Washers over the Strainer Body. Secure the Strainer Body with the Nut. **DO NOT OVERTIGHTEN.** When the Strainer Body is tightened securely to the Bowl, clean off any excess plumber's putty.



Attach the Gasket and Tailpiece to the Strainer Body. **DO NOT OVERTIGHTEN.**



**IMPORTANT!  
DO NOT OVERTIGHTEN  
DRAIN ASSEMBLY!**


# INSTALLATION INSTRUCTIONS

MODEL NUMBER : 570

## CHROME LEVER-HANDLE FAUCET

### INSTALLATION GUIDELINES

#### ENGLISH



1. Unscrew the fixed parts ( such as (#6) fix nut, (#5) brass washer, (#4) rubber washer ) from the faucet.
2. Have the two (#7) flexible hoses screwed to the hot/cold water outlet accordingly.
3. Put the (#1) Main body and (#2) Base of the main body from the top to line up with the reserved hole on basin.
4. From the bottom, secure the (#4) rubber washer, (#5) brass washer in the order by screwing the (#6) fix nut to the (#3) retaining mounting tube.

#### ESPAÑOL

1. Desatorille las partes que contengan roscas (como por ejemplo #6, atornillador de cobre #5 y atornillador de plástico #4) de la llave.
2. Conecte las dos mangueras (parte #7) a la conexión de el agua caliente/fría como sea necesario.
3. Ponga la llave principal (parte #1) y la base (parte #2) en el hoyo de arriba designado específicamente para este uso.
4. De la parte de abajo del lavado, apriete en orden el atornillador de plástico (parte #4) luego el atornillador de cobre (parte #5) reforzándolos con la rosca #6 en el tubo de montaje (parte #3).


#### FRANÇAIS

1. Dévissez les pièces fixes (telles que l'écrou de difficulté #6, la rondelle #5 en laiton, et la rondelle #4 en caoutchouc) du robinet.
2. Ayez les deux tuyaux #7 flexibles vissés à la sortie eau chaude/froide en conséquence.
3. Mettez le corps #1 principal et la base #2 du corps principal à partir du dessus pour aligner avec le trou réservé en bassin.
4. Du fond, fixez la rondelle #4 en caoutchouc et la rondelle #5 en laiton dans l'ordre en vissant l'écrou de la difficulté #6 au #3 maintenant le tube de support.

### CORRECT HOSE CONNECTIONS FOR VACUUM BREAKER

ESPAÑOL: CONEXIONES CORRECTAS de la MANGUERA para el TRITURADOR del VACÍO

FRANÇAIS: RACCORDEMENTS CORRECTS de TUYAU pour le BRISEUR de VIDE



ENGLISH: Arrows on the vacuum breaker indicate directional flow of water. Device will leak and not work properly if installed with water flow reversed.

ESPAÑOL: Las flechas en el triturador del vacío indican el flujo direccional de agua. El dispositivo se escapará y no funcionará correctamente si está instalado con la corriente invertida.

FRANÇAIS: Les flèches sur le briseur de vide indiquent l'écoulement directionnel de l'eau. Le dispositif coulera et ne fonctionnera pas correctement s'installé avec l'écoulement d'eau a renversé.

### VACUUM BREAKER WILL LEAK IF WATER FLOW IS REVERSED

**collins**




Jeffco Salon Equipment, LLC  
2000 Bowser Road  
Cookeville, TN 38506  
[www.jeffcosalonequipment.com](http://www.jeffcosalonequipment.com)

# INSTALLATION INSTRUCTIONS

MODEL NUMBER : 570

CHROME LEVER-HANDLE FAUCET

## ILLUSTRATED PARTS LIST



### ENGLISH:

- 01. INDEX BUTTON
- 02. HANDLE SCREW
- 03. HANDLE
- 04. ESCUTCHEON
- 05. ESCUTCHEON NUT
- 06. CARTRIDGE: VALVE
- 07. VALVE SLEEVE
- 08. DRAIN
- 09. SPOUT ADAPTER
- 10. SPOUT BASE
- 11. O-RING
- 12. RUBBER WASHER
- 13. BRASS WASHER
- 14. SUPPLY NUT
- 15. STEEL HOSE
- 16. RUBBER WASHER

### ESPAÑOL:

- 01. Tornillo de Seguridad
- 02. Tornillo de Ajuste
- 03. Manija
- 04. Abrazadera
- 05. Abrazadera con Ajuste
- 06. Válvula de Soporte
- 07. Válvula Cobertora
- 08. Destape
- 09. Adaptador de Destape
- 10. Base de Destape
- 11. Anillo "O"
- 12. Abrazadera de Plástico
- 13. Abrazadera de Cobre
- 14. Tuerca
- 15. Manguera de Acero
- 16. Arandela de goma

### FRANÇAIS:

- 01. BOUTON D'INDEX
- 02. VIS DE POIGNEE
- 03. POIGNEE
- 04. CACHE
- 05. ÉCROU DE CACHE
- 06. CARTOUCHE - VALVE
- 07. DOUILLE DE VALVE
- 08. DRAIN
- 09. ADAPTEUR DE BEC
- 10. BASE DE BEC
- 11. JOINT CIRCULAIRE
- 12. RONDELLE EN CAOUTCHOUC
- 13. RONDELLE EN LAITON
- 14. ÉCROU D'APPROVISIONNEMENT
- 15. TUYAU EN ACIER
- 16. RONDELLE EN CAOUTCHOUC